


BSD 4-14N CATV loop-through outlet 14 dB | 5...1006 MHz



- ✓ Suitable for broadband return path
- ✓ Surface treated

Order information

Type	BSD 4-14N
Order no.	BSD00414N
GTIN	7611682007336
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Tap method	Double directional coupler
Through loss	2.0...3.8 dB
Trunk line	
Frequency range input	5...1006 MHz
Through loss @ 5...1006 MHz	<3.8 dB
Isolation internal	≥ 25 dB
Frequency range output	5...1006 MHz
Suitable cables (Inner conductor outer diameter)	0.63...1.13 mm 4.7...7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	5...1006 MHz
Tap loss	14 dB ±2 dB
Radio connector	
Connector type	IEC-female
Frequency range	5...1006 MHz
Tap loss	14 dB ±2 dB
General	
Dimensions (W × H × D) appr.	70 × 66 × 32 mm
Weight	0.091 kg

Suitable products

[TZU 2-00 Cover plate | TV/R | single piece](#)

[TZU 1-00 Surface frame](#)

[TZU 2-10 Cover plate | TV/R | two-parts](#)

[TZU 1-10 Surface frame](#)

[TZU 3-00 Terminating resistor](#)