

GigaLine[®] I-V(ZN)H - Dca

Mini breakout indoor cable, STB900

E9/125 bend insensitive OS2




Illustration similar

Description

Fibre optic indoor cable, with buffered fibres, mini break out. Colour code acc. to EIA/TIA 598C.

Properties / applications

Indoor cable for fixed installation.

Connecting cable and patch cord for generic cabling systems acc. to ISO/IEC 11801 and EN 50173. Ideal for all applications of Classes OF 300 to OF 2000. Suitable for direct connector mounting with adhesive technology. Unsuitable for crimp connectors.

Laying

For indoor installation in conduits, tubes or on cable trays.

Construction

Product name	GigaLine [®] I-V(ZN)H - Dca
Fibre quality	E9...10/125 0,36F4/0,22H18-Low OH OS2
Tube	Semi tight buffer 0.9 mm
Strain relief (over all)	Non metallic, aramide
Outer sheath (colour)	Colza yellow

Mechanical characteristics (cable)

Bending radius (static)	10x outer diameter
Bending radius (dynamic)	15x outer diameter
Bending radius single element	30 mm
Crush resistance (short term)	1000 (N/100mm)
Crush resistance (long term)	500 (N/100mm)
Max. strain relief	800 N

Thermal characteristics (cable)

Temperature (transport / storage)	-25 °C up to +70 °C
Temperature during installation	-5 °C up to +50 °C
Temperature after installation	-10 °C up to +70 °C

GigaLine[®] I-V(ZN)H - Dca

Mini breakout indoor cable, STB900

E9/125 bend insensitive OS2

Standards, certificates and approvals

Fibre standard	OS2 ITU-T 652.D + G657.A1 IEC 60793-2 B1.3
Cabling standard	EN 50173, ISO/IEC 11801
Fire class	Dca s2 d2 a2 acc. to EN 50575 / 50399
DoP	CDESK0000083
Flame retardancy	IEC 60332-1-2, IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1
Acidity of the combustion gases	IEC 60754-2
Smoke density	IEC 61034
Chemical continuance	Free of hazardous substances acc. to RoHS 2011/65/EU

Part number	Number of fibres	Weight	Fire load	Outer diameter	Single element Ø ca.
LKD8MC70012000	4	21,0 kg/km	0,47 MJ/m	5,6 mm	0,9 mm