

# GigaLine<sup>®</sup> DCLink splice module

## 6 LC quad, 7 HP

OM4 G50/125



Illustration similar

### Description

DCLink splice module 7 HP for the termination of transmission lines by splicing pigtails, incl. splice cassette and excess length cassette for loose tubes.

### Properties / applications

Tool-free installation in module racks and CP-housings (snap in). Suitable for the installation from the front and from behind. For 12 applications with LC duplex OM4.

### Construction

|                        |                                                                |
|------------------------|----------------------------------------------------------------|
| Material (housing)     | Stainless steel                                                |
| Material (front panel) | Steel sheet, coloured zinc plated                              |
| Front colour           | Black                                                          |
| Fixation               | Snap in                                                        |
| Connector standard     | IEC 61754-20 (LC)                                              |
| Adapter                | Heather violet, Plastic, slotted full floating sleeve, ceramic |
| Cable fixation         | By cable ties                                                  |

### Optical characteristics (connector A / connector B)

|                       |         |
|-----------------------|---------|
| Insertion loss (max.) | 0,3 dB  |
| Insertion loss (typ.) | 0,15 dB |
| Return loss (min.)    | 35 dB   |

### Dimensions

|                |        |
|----------------|--------|
| Width          | 106 mm |
| Height         | 35 mm  |
| Depth          | 275 mm |
| Mounting depth | 255 mm |

### Labelling

Characters 1 to 12

### Standards, certificates and approvals

|                    |                                    |
|--------------------|------------------------------------|
| Fibre standard     | OM4 ITU-T 651<br>IEC 60793-2 A1a.3 |
| Connector standard | IEC 61754-20 (LC)                  |
| Cabling standard   | EN 50173, ISO/IEC 11801            |

### Equipping

LC quad

# GigaLine<sup>®</sup> DClick splice module

## 6 LC quad, 7 HP

OM4 G50/125

### Scope of supply

- 1 module with front panel
- adapters
- pigtails
- 1 splice cassettes with cover
- 2 splice protection holders
- 1 excess-length cassette with cover
- 1 guid clip
- mounting material

### Accessories (optional)

- Protection tubes for loose tubes with a max. outer diameter of 2.4 mm (LKD7KMKC0620000)
- Splice holder for shrink splice protectors for 6x 3mm or 12x 2mm shrink splice protectors (LKD9D0002580000)
- Heat shrink splice protection diameter: 3 mm (LKD9D0003080000)
- Heat shrink splice protection diameter: 2 mm (LKD9D0003090000)

### Coupling colour

Heather violet

### Part number

LKD9SEX00030000