



MPOptimate® Trunk Cable, 12 fiber, multimode OM3, MPO-MPO female, XG, straight, 20 m, aqua

OBSOLETE

Replaced By:

AJXMPMPAD

OM4 MP012 (female) to MPO12 (female), Fiber Trunk Cable Assembly, 12-Fiber, Method A, Low Smoke Zero Halogen

Product Classification

Regional Availability	Asia Australia/New Zealand China EMEA Europe India
Portfolio	NETCONNECT®
Product Type	Fiber trunk cable assembly
Product Brand	MPOptimate®

General Specifications

Color, boot A	Black
Color, boot B	Black
Color, connector A	Beige
Color, connector B	Beige
Connector A, quantity	1
Connector B, quantity	1
Interface, Connector A	MPO-12/UPC Female
Interface, Connector B	MPO-12/UPC Female
Jacket Color	Aqua
Polarity	Pairs, straight
Total Fibers, quantity	12

Dimensions

2-2055611-0

Cord Length	20 m 65.617 ft
Diameter Over Jacket	6.4 mm 0.252 in

Optical Specifications

Fiber Mode	Multimode
Fiber Type	OM3
Insertion Loss, maximum, connector A	0.35 dB
Insertion Loss, maximum, connector B	0.35 dB
Return Loss, minimum, connector A	28 dB
Return Loss, minimum, connector B	28 dB

Environmental Specifications

Environmental Space	Low Smoke Zero Halogen (LSZH)
----------------------------	-------------------------------

Packaging and Weights

Packaging quantity	1
---------------------------	---

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted

