

MPO Trunk Cable, 2x12 fiber, singlemode, MPO female-female, LSZH, straight, 20 m

OBSOLETE

Replaced By:

AJGMPMPAF

Singlemode MPO12 (female) to MPO12 (female), Fiber Trunk Cable Assembly, 24-Fiber, Method A, Low Smoke Zero Halogen

Product Classification

Regional Availability	Asia Australia/New Zealand China EMEA Europe India
Portfolio	NETCONNECT®
Product Type	Fiber trunk cable assembly
Product Brand	MPOptimate®

General Specifications

Color, boot A	Black
Color, boot B	Black
Color, connector A	Green
Color, connector B	Green
Connector A, quantity	2
Connector B, quantity	2
Interface, Connector A	MPO-12/APC Female
Interface, Connector B	MPO-12/APC Female
Jacket Color	Yellow
Polarity	Pairs, straight
Total Fibers, quantity	24

Dimensions

Cord Length	20 m 65.617 ft
Diameter Over Jacket	8 mm 0.315 in

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	OS2

2-2055713-0

Insertion Loss, maximum, connector A	0.75 dB
Insertion Loss, maximum, connector B	0.75 dB
Return Loss, minimum, connector A	35 dB
Return Loss, minimum, connector B	35 dB

Environmental Specifications

Environmental Space	Low Smoke Zero Halogen (LSZH)
----------------------------	-------------------------------

Packaging and Weights

Packaging quantity	1
---------------------------	---

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted

